1. 首先在主界面布局文件中增加一个 ProgressBar, 将 ProgressBar 和之前的更新按钮 ImageView 放在一起, 并且写在 FrameLayout 下。如图

```
android:id="@+id/title city name"
    android:layout_width="fill parent"
    android:layout_height="fill_parent"
    android:layout_toRightOf="@id/city_seperator"
    android:gravity="center_vertical"
    android:paddingLeft="5dip"
    android:textColor="#ffffffff"/>
<FrameLayout</pre>
    android:id="@+id/updateFrame"
    android:layout_width="45.0dip'
    android:layout_height="45.0dip"
    android:layout_alignParentRight="true"
    android:layout_gravity="center">
    <ImageView</pre>
        android:id="@+id/title_update_btn"
        android:layout_width="fill_parent"
        android:layout_height="fill_parent"
        android:src="@drawable/title update"
        android:visibility="visible" />
    <ProgressBar</pre>
        android:id="@+id/title update_progress"
        android:layout width="fill parent"
        android:layout_height="fill_parent"
        android:visibility="invisible'
        android:indeterminateBehavior="repeat"
        android:indeterminateDrawable="@drawable/animated"
        style="@style/title_update_progressbar_style"/>
</FrameLayout>
```

注意和其他按钮或者 button 的位置,比如和分享按钮的位置要进行代码的修改


```
<ImageView
    android:id="@+id/title_share"
    android:layout_width="45.0dip"
    android:layout_height="45.0dip"
    android:layout_toLeftOf="@id/updateFrame"
    android:src="@drawable/title_share" />
```

2. 编写相关的资源文件

正常情况下应该在 res 下创建 animator, 编写相关文件, 但我的会报错. 我就在 drawable 下创建资源文件。

右键 drawable, new 一个 drawable Resource file, 注意 root element 换成 <mark>animated-rotate</mark>

资源文件代码



3. java 后台

在主 activity 中,首先定义一个 bar。

```
private ProgressBar progressBar;
```

然后在 oncreate 中为添加它

```
progressBar=(ProgressBar)findViewById(R.id.title_update_progress);
```

然后走 onclick 事件,一点击刷新按钮,此时应该 update_btn 应该隐藏,progressbar 不隐藏,

```
//单击事件如果是刷新天气应用发生
if (view.getId() == R.id.title_update_btn) {
    mUpdateBtn.setVisibility(View.GONE);
    progressBar.setVisibility(View.VISIBLE);
    //通过SharedPreferences读取塘市id.如果没有定义则缺省为101010100(出京城市)
    SharedPreferences sharedPreferences = getSharedPreferences( name: "cityCodePreferenced",
    String cityCode = sharedPreferences.getString( key: "cityCode", defValue: "");
    if(!cityCode.equals("")){
        Log.d( tag: "ksning".cityCode);
        queryWeatherCode(cityCode);
    }else{
        queryWeatherCode(cityCode: "101010100");
    }

if (NetUtil.getNetworkState( context this) != NetUtil.NETWORN_NONE) {
        Log.d( tag: "ksningWeather", imsg: "网络大阪");
        queryWeatherCode(cityCode);
    } else {
        Log.d( tag: "ksningWeather", imsg: "网络失败");
        Toast.makeText( context MyActivity.this, text "网络失败", Toast.LENGTH_SHORT).show();
    }
}
```

最后,他们内部处理好之后,在传给前台界面,更新界面,走UpdateTodayWeather()方法,此时,就让 update_btn 显示,progressBar 隐藏。

```
void updateTodayWeather(TodayWeather todayWeather){

if(mUpdateBtn.getVisibility()==View.GONE&&progressBar.getVisibility()==View.VISIBLE){
    progressBar.setVisibility(View.GONE);
    mUpdateBtn.setVisibility(View.VISIBLE);
}

city_name_Tv.setText(todayWeather.getCity())+"天(");
cityTv.setText(todayWeather.getCity());
timeTv.setText(todayWeather.getUpdatetime()+"没值");
humidityTv.setText("MUE:"+todayWeather.getShidu());
weekTv.setText(todayWeather.getDate());
pmDataTv.setText(todayWeather.getPm25());
pmQualityTv.setText(todayWeather.getQuality());
temperatureTv.setText(todayWeather.getType());
windTv.setText(todayWeather.getType());
windTv.setText(todayWeather.getType());
temperatureRangeTv.setText(todayWeather.getFengli());
temperatureRangeTv.setText(todayWeather.getLow()+"~"+todayWeather.getHigh());
Toast.makeText(context:this, text:"更新成功", Toast.LENGTH_SHORT).show();
```